




IP66 Industrial Range Mounting Enclosures and Covers

Data 20 Specification 20 24









[DESCRIPTION]

Connected Switchgears' mounting bases are designed for the use with all IMPACT and IMPACT S Series IP66 Industrial Switchgear. Mounting bases are 60mm deep and have standard 84mm centre screw fixings. Designed to achieve an IP66 protection rating when used with appropriately suited products. Manufactured from impact resistant polycarbonate material and supplied with cross bars and screw caps. Available up to 9 gang. Polycarbonate cover plates to suit in 1 and 2 gang also available.

[FEATURES]

- Impact Resistant
- Ample Volume for Wiring
- Ample Conduit Entries
- Cross Bars and Screw Caps Included

[TECHNICAL PARAMETERS]

- IP Protection: IP66
- Operating Temp: -40°C 80°C
- Flame Rating: UL-94HB
- Material: UV Resistant/Impact Resistant Polycarbonate

[COMPLIANCE]

AS/NZS 60529:2004

[IMAGES]



CME2



ME6



[SPECIFICATIONS]

Product Code	No. of Gangs	Length (mm)	Width (mm)	Depth (mm)	Mounting Points	Conduit Entries
ME1S	1	98	98	37	4	2 x 25mm, 2 x 32mm
MEI	1	98	98	62	4	2 x 25mm, 2 x 32mm
ME2S	2	197	98	38	8	3x 25mm, 3 x 32mm
ME2	2	197	98	60	8	3x 25mm, 3 x 32mm
ME3	3	294	98	61	12	4 x 25mm, 2 x 32mm
ME4	4	197	197	61	16	6 x 25mm, 1 x 32mm, 1 x 40mm
ME6	6	294	197	61	24	4 x 25mm, 4 x 32mm, 2 x 40mm
ME8	8	392	197	61	32	6 x 25mm, 4 x 32mm, 2 x 40mm
ME9	9	294	294	61	28	7 x 25mm, 5 x 32mm, 2 x 40mm
CME1	1	98	98	30	-	-
CME2	2	197	98	30	-	-

[WARRANTY]

Connected Switchgear IMPACT series of product come with a trusted 5 Year In House Warranty. That means that you have peace of mind knowing that if a fault develops within a five year period, Connected Group Australia will cover the cost of replacing the product and it's installation.*

* See our website for full terms and conditions www.connectedswitchgear.com.au

